







Benefits for your nursing staff and your residents ...

- Carrier frame and lifting column made out of aluminium and steel
- Extra light and easy to maneuver
- ✓ High-quality lockable double castors
- ✓ Electrical height adjustment and electrically spreadable carrier frame
- ✓ 2-point sling spreader bar can be lowered to the floor
- ✓ No unsettling pendular or rotational movements during lifting and transferring thanks to the patented anti-rotation mechanism (ARM)
- Can easily pass underneath both bath tubs and care beds
- Hand control with display of the battery charge status
- Working in an ergonomic and health-orientated manner, as no manual lifting is required
- ✓ Large choice of comfortable loop slings of different sizes
- ✓ Also available with patient scale





Also available with a 4-point sling spreader bar

Technical data	Model Classic 185	Model Classic 205
Carrier frame (length/height)	1.290 mm / 125 mm	1.290 mm / 125 mm
Inner width (closed/spread)	540 mm / 1.040 mm	540 mm / 1.040 mm
Outer width (closed/spread)	700 mm / 1.180 mm	700 mm / 1.180 mm
Total width of the lift (carrier frame closed)	700 mm	700 mm
Lifting range	1.400 mm	1.400 mm
Max. patient weight	185 kg	205 kg
SWL	185 kg	205 kg
Drive	24V LINAK drive	24V LINAK drive

Accessories / Options

Patient scale		
Transfer slings with loops (available in different sizes, standard size S-XXL)		
Bathing slings with loops (available in different sizes, standard size S-XXL)		
Toilet slings with loops (available in different sizes, standard size S-XL)		
Soft slings with loops (available in different sizes, standard size S-XL)		
Spare battery 24 V		
External wall charging unit		



BEKA Hospitec GmbH | Am Rübenmorgen 3 | 35582 Wetzlar-Dutenhofen
Tel +49 641 922 20-0 | E-Mail info@beka-hospitec.com
www.beka-hospitec.com

